



晶采光電科技股份有限公司
AMPIRE CO., LTD.

SPECIFICATIONS FOR LCD MODULE

CUSTOMER	
CUSTOMER PART NO.	
AMPIRE PART NO.	AM-1024600K1TMQW-T00H
APPROVED BY	
DATE	

- Approved For Specifications
 Approved For Specifications & Sample

AMPIRE CO., LTD.
4F., No.116, Sec. 1, Xintai 5th Rd., Xizhi Dist., New Taipei City 221,
Taiwan (R.O.C.)
22181 新北市 汐止區 新台五路一段 116 號 4 樓(東方科學園區 A 棟)
TEL:886-2-26967269 , FAX:886-2-26967196 or 26967270

APPROVED BY	CHECKED BY	ORGANIZED BY

RECORD OF REVISION

Revision Date	Page	Contents	Editor
2012/6/28	--	New Release	Kokai

1 Features

7 inch Amorphous-TFT-LCD (Thin Film Transistor Liquid Crystal Display) module. This module is composed of a 7" TFT-LCD panel, LED backlight, LED driver unit , **Projective capacitive touch panel** and power circuit unit.

- (1) Construction: 7" a-Si TFT active matrix, White LED Backlight and power & LED driver.
- (2) Resolution (pixel): 1024(R.G.B) X600
- (3) Number of the Colors : 16M colors (R , G , B 6 bit digital each)
- (4) LCD type : Transmissive , normally White
- (5) Interface: LVDS interface 6bit (default), 8bit by jumper setting.
- (6) Power Supply Voltage: 3.3V for logic voltage, 5V or 12V for LED driver power voltage.
- (7) Viewing Direction: 6 O'clock (The direction it's hard to be discolored)
- (8) **Projective capacitive touch panel. USB interface.**

2 PHYSICAL SPECIFICATIONS

Item	Specifications	unit
LCD size	7 inch (Diagonal)	
Resolution	1024 x 3(RGB) x 600	dot
Dot pitch	0.05(W) x 0.15(H)	mm
Active area	153.6(W) x 90.0(H)	mm
Module size	165. 5(W) x 104.44(H) x 8.76(D)	mm
Surface treatment	Hard Coating, Glare	
Color arrangement	RGB-stripe	
interface	LVDS	
Brightness	450	cd/m ²
Weight	TBD	g

3 ABSOLUTE MAX. RATINGS

Item	Symbol	Values		UNIT	Note
		Min.	Max.		
Power voltage	VCC	-0.3	4.2	V	
	VLED	-0.3	14		
Operation temperature	TOP	-20	70	°C	
Storage temperature	TST	-30	80	°C	

The following values are maximum operation conditions , If exceeded , it may cause faulty operation or damage

4 ELECTRICAL CHARACTERISTICS

4.1 Typical Operation Conditions

Item	Symbol	Values			Unit	Remark	
		MIN	TYP	MAX			
Power Voltage	V_{CC}	3.0	3.3	3.6	V	Note 1,2	
Power Consumption	I_{CC}	--	150	--	mA	Note 1,2 $V_{CC}=3.3V$	
Logic Input Voltage	Input Voltage	V_{IN}	0	-	V_{CC}	V	
	Logic input high voltage	V_{TH}	$0.7V_{CC}$	-	V_{CC}	V	Note 3
	Logic input low voltage	V_{TL}	GND	-	$0.3V_{CC}$	V	Note 3

Note 1: Value for Power Board combined panel.

Note 2: VCC setting should match the signals output voltage (refer to Note 3) of customer's system board.

Note 3: LVDS.

4.2 LED Driving Conditions

Item	Symbol	Values			Unit	Note
		Min.	Typ.	Max.		
LED Driver Power Voltage	V_{LED}	5	--	12	V	
LED Driver Current Consumption	I_{LED}	--	800	--	mA	$V_{LED}=5V$ $ADJ=3.3V$ (duty 100%)
		--	350	--	mA	$V_{LED}=12V$ $ADJ=3.3V$ (duty 100%)
ADJ Input Voltage	V_{ADJ}	3.3	--	5	V	duty=100% Note(3)
LED voltage	V_{AK}	15.5	16.5	17.5	V	Note(1)
LED forward Current	I_{AK}	--	180	--	mA	$T_a=25^{\circ}C$
LED life time	--	--	30,000	--	Hr	Note(2)


Note (1) The constant current source is needed for white LED back-light driving.

When LCM is operated over 60 deg.C ambient temperature, the I_{LED} of the LED back-light should be adjusted .

Note (2) Brightness to be decreased to 50% of the initial value.

Note (3) V_{LEDADJ} is PWM signal input. It is for brightness control.


There are 3 Groups LED shown as below , $V_{AK} = 16.5V$, $I_{AK} = 180mA$.




Brightness to be decreased to 50% of the initial value.

4.3 Power Sequence

a. Power on:



b. Power off:




5 Optical Specifications

Item	Symbol	Condition	Values			Unit	Note
			Min.	Typ.	Max.		
Viewing angle (CR \geq 10)	θ L	$\Phi = 180^\circ$ (9 o'clock)	65	75	--	degree	Note1
	θ R	$\Phi = 0^\circ$ (3 o'clock)	65	75	--		
	θ T	$\Phi = 90^\circ$ (12 o'clock)	65	70	--		
	θ B	$\Phi = 270^\circ$ (6 o'clock)	65	75	--		
Response time	TON	Normal $\theta = \Phi = 0^\circ$	--	10	20	msec	Note3
	TOFF		--	15	30	msec	
Contrast ratio	CR		500	700	--	--	Note4
Color chromaticity	WX		0.249	0.299	0.349	--	Note5
	WY		0.273	0.323	0.373	--	Note6
Luminance	L		360	450	--	cd/m ²	Note6
Transmittance	Tr		--	3.5	--	%	

Test Conditions:


1. Vled = 12V, IL = 240mA (Backlight current), the ambient temperature is 25°C.
2. The test systems refer to Note 2.

Note 1 : Definition of viewing angle range




Note 2 : Definition of optical measurement system.

The optical characteristics should be measured in dark room. After 30 minutes operation, the optical properties are measured at the center point of the LCD screen. (Response time is measured by Photo detector TOPCON BM-7, other items are measured by BM-5A/Field of view : 1° / Height : 500 mm.)



Note 3 : Definition of Response time

The response time is defined as the LCD optical switching time interval between “White” state and “Black” state. Rise time (T_{ON}) is the time between photo detector output intensity changed from 90% to 10%. And fall time (T_{OFF}) is the time between photo detector output intensity changed from 10% to 90%.



Note 4 : Definition of contrast ratio

$$\text{Contrast ratio (CR)} = \frac{\text{Luminance measured when LCD on the "White" state}}{\text{Luminance measured when LCD on the "Black" state}}$$

Note 5 : Definition of color chromaticity (CIE1931)

Color coordinated measured at center point of LCD.

Note 6 : All input terminals LCD panel must be ground when measuring the center area of the panel.

6 Interface

6.1 CN2 : TFT LCD Panel Driving Section

Pin No.	Symbol	I/O	Description	Note
1	VDD	P	Power Voltage for Logic: 3.3V	
2	VDD	P	Power Voltage for Logic: 3.3V	
3	U/D	I	Vertical Reverse Scan Control	
4	L/R	I	Horizontal Reverse Scan Control.	
5	IN0-	I	- LVDS differential data input	
6	IN0+	I	+ LVDS differential data input	
7	GND	P	Ground	
8	IN1-	I	- LVDS differential data input	
9	IN1+	I	+ LVDS differential data input	
10	GND	P	Ground	
11	IN2-	I	- LVDS differential data input	
12	IN2+	I	+ LVDS differential data input	
13	GND	P	Ground	
14	CLK-	I	- LVDS differential data input	
15	CLK+	I	+ LVDS differential data input	
16	GND	P	Ground	
17	IN3-	I	- LVDS differential data input	
18	IN3+	I	+ LVDS differential data input	
19	VLED	P	Power supply for backlight: 5V OR 12V	
20	LEDADJ	I	LED PWM signal	(1)

I : input, O : output, P : power

6.2 CN3 : LED Back-light Driver Section

Pin No.	Symbol	I/O	Description	Note
1	VLED	P	Power supply for backlight: 5V OR 12V	
2	GND	P	Power Ground	
3	NC	--	No Connection	
4	Dimming	I	LED PWM signal same as LEDADJ	(1)
5	NA	--	No Connection	

NOTE :

(1) Pin3: ADJ is PWM signal input. It is for brightness control.

ITEM	SYMBOL	MIN	TYP	MAX	UNIT
ADJ signal frequency	f _{PWM}	10	--	100	KHz
ADJ signal logic level High	VIH	2	--	VLED	V
ADJ signal logic level Low	VIL	0	--	0.5	V

7 Projected capacitive-type Touch panel specification

7.1 Touch panel ABSOLUTE MAX. RATINGS

Item	Symbol	Values		UNIT	Note
		Min.	Max.		
Touch Panel Power voltage	VIN	--	5.6	V	

7.2 Touch panel Electrical Characteristics

Item	Symbol	Values			UNIT	Note
		Min.	Typ.	Max.		
Touch Panel Power voltage	VIN	4.5	5	5.5	V	
Touch Panel power supply at Normal operation Mode	IVIN	-	TBD	-	mA	

7.3 Touch panel Interface

CN6 :

Pin No.	Symbol	Description	Note
1	DGND	Power GND	
2	DA-	USB differential signal	
3	DA+	USB differential signal	
4	VIN	Power Supply input 5V	
5~6	NA	No Connection	



CN7 :

Pin No.	Symbol	Description	Note
1	VDD	These pins are for Touch Panel controller programming. Don't connect to and signals.	
2	ICE_DA		
3	ICE_CK		
4	RESET		
5~6	DGND		

8 TIMING CHARACTERISTICS


8.1 AC Electrical Characteristics

Parameter	Symbol	Values			Unit	Remark
		MIN	TYP	MAX		
Clock frequency	R_{xFCLK}	40.8	51.2	71		
Input data skew margin	T_{RSKM}	500	--	--		
Clock high time	T_{LVCH}	--	$4/(7 * R_{xFCLK})$	--		
Clock low time	T_{LVCL}	--	$3/(7 * R_{xFCLK})$	--		



8.2 DC Electrical Characteristics


Item	Symbol	Values			Unit	Note
		Min.	Typ.	Max.		
Differential input high Threshold voltage	R_{xVTH}	-	-	+0.1	V	$R_{xVCM}=1.2V$
Differential input low Threshold voltage	R_{xVTL}	-0.1	-	-	V	
Input voltage range (singled-end)	R_{xVIN}	0	-	2.4	V	
Differential input common mode voltage	R_{xVCM}	$ V_{ID} /2$	-	$2.4- V_{ID} /2$	V	
Differential voltage	$ V_{ID} $	0.2	-	0.6	V	
Differential input leakage current	RV_{xliz}	-10	-	+10	μA	




8.3 Timing

Item	Symbol	Values			Unit	Note
		Min.	Typ.	Max.		
Clock Frequency	fclk	40.8	51.2	67.2	MHz	Frame rate =60Hz
Horizontal display area	thd	1024			DCLK	
HS period time	th	1114	1344	1400	DCLK	
HS Blanking	thb	90	320	376	DCLK	
Vertical display area	tvd	600			H	
VS period time	tv	610	635	800	H	
VS Blanking	thb	10	35	200	H	

6bit LVDS input



8bit LVDS input



9 RELIABILITY TEST CONDITIONS

(Note 3)

Item	Test Conditions	Note
High Temperature Storage	Ta = 80°C 240 hrs	Note 1,4
Low Temperature Storage	Ta = -30°C 240 hrs	Note 1,4
High Temperature Operation	Ts = 70°C 240 hrs	Note 2,4
Low Temperature Operation	Ta = -20°C 240 hrs	Note 1,4
Operate at High Temperature and Humidity	+60°C, 90%RH 240 hrs	
Thermal Shock	-30°C /30 min ~ +80°C /30 min for a total 100 cycles, Start with cold temperature and end with high temperature	

Note 1 : Ta is the ambient temperature of samples.

Note 2 : Ts is the temperature of panel's surface.

Note 3 : In the standard condition, there shall be no practical problem that may affect the display function. After the reliability test, the product only guarantees operation, but don't guarantee all of the cosmetic specification.

Note 4 : Before cosmetic and function test, the product must have enough recovery time, at least 2 hours at room temperature.

10 General Precautions

10.1 Safety

Liquid crystal is poisonous. Do not put it your mouth. If liquid crystal touches your skin or clothes, wash it off immediately by using soap and water.

10.2 Handling

1. The LCD panel is plate glass. Do not subject the panel to mechanical shock or to excessive force on its surface.
2. The polarizer attached to the display is easily damaged. Please handle it carefully to avoid scratch or other damages.
3. To avoid contamination on the display surface, do not touch the module surface with bare hands.
4. Keep a space so that the LCD panels do not touch other components.
5. Put cover board such as acrylic board on the surface of LCD panel to protect panel from damages.
6. Transparent electrodes may be disconnected if you use the LCD panel under environmental conditions where the condensation of dew occurs.
7. Do not leave module in direct sunlight to avoid malfunction of the ICs.

10.3 Static Electricity

1. Be sure to ground module before turning on power or operation module.
2. Do not apply voltage which exceeds the absolute maximum rating value.

10.4 Storage

1. Store the module in a dark room where must keep at $+25\pm 10^{\circ}\text{C}$ and 65%RH or less.
2. Do not store the module in surroundings containing organic solvent or corrosive gas.
3. Store the module in an anti-electrostatic container or bag.


10.5 Cleaning

1. Do not wipe the polarizer with dry cloth. It might cause scratch.
2. Only use a soft sloth with IPA to wipe the polarizer, other chemicals might permanent damage to the polarizer.

10.6 Others

1. AMIPRE will provide one year warrantee for all products and three months warrantee for all repairing products.

11 OUTLINE DIMENSION



A Block

CN6		CN7	
1	DGND	1	VDD
2	DA-	2	ICE_DA
3	DA+	3	ICE_CK
4	VIN	4	RESET
5	NA	5	DGND
6	NA	6	DGND


CN2			
1	VDD	11	IN2-
2	VDD	12	IN2+
3	U/D	13	GND
4	L/R	14	CLK-
5	INO-	15	CLK+
6	INO+	16	GND
7	GND	17	IN3-
8	IN1-	18	IN3+
9	IN1+	19	VLED
10	GND	20	ADJ

CN3	
1	VLED
2	GND
3	NC
4	Dimming
5	NA

Note:

- Unless indicated, Tolerance "±0.3"
- UV Glue For OLB Protection.
- CN2:P1.0 20Pin/CP100-S20G-H16 or Equivalent
- CN1:P0.5 40Pin/CS050-40ZST-H12-U or Equivalent
- CN3: ENTERY 3808K-F05N-03L or Equivalent, Mating Connector: ENTERY H208K-P05N-02B or Equivalent
- LCD 800X3(R.G.B)x480=> 7.0" Digital TFT LCD


REV	REVISION RECORD	DATE	NAME
0	NEW RELEASE	02-17-12	EMILY



NO.	DESCRIPTION	7	8	9	10	11	12	TOLERANCE GRADE(±)	A	B	DIM. MM	DWN.	DATE	TITLE
1	1024600K LCM +800480RB T/P	7	8	9	10	11	12					EMILY	02-17-12	1024600K1-T
2												CHK.		(7.0"+LVDS+LED_Driver+T/P)
3												APPD.		DWG. NO. *120247MA
4														SHEET 1 OF 1
5														
6														



REV	REVISION RECORD	DATE	NAME
0	NEW RELEASE	02-17-12	EMILY




A Block

CN6		CN7	
1	DGND	1	VDD
2	DA-	2	ICE_DA
3	DA+	3	ICE_CK
4	VIN	4	RESET
5	NA	5	DGND
6	NA	6	DGND

CN2			
1	VDD	11	IN2-
2	VDD	12	IN2+
3	U/D	13	GND
4	L/R	14	CLK-
5	INO-	15	CLK+
6	INO+	16	GND
7	GND	17	IN3-
8	IN1-	18	IN3+
9	IN1+	19	VLED
10	GND	20	ADJ


CN3	
1	VLED
2	GND
3	NC
4	Dimming
5	NA



Back View

Note:

1. Unless indicated, Tolerance "±0.3"
2. UV Glue For OLB Protection.
3. CN2:P1.0 20Pin/CP100-S20G-H16 or Equivalent
4. CN1:P0.5 40Pin/CS050-40ZST-H12-U or Equivalent
5. CN3: ENTERY 3808K-F05N-03L or Equivalent, Mating Connector: ENTERY H208K-P05N-02B or Equivalent
6. LCD 800X3(R.G.B)x480=> 7.0" Digital TFT LCD



NO.	DESCRIPTION	7	8	9	10	11	12	TOLERANCE GRADE(±)	A	B	DIM. MM	DWN. EMILY	DATE 02-17-12	TITLE		
1	1024600K LCM +800480RB T/P													1024600K1-T		
2														(7.0"+LVDS+LED Driver+T/P)		
3																
4																
5																
6																
												PARTS NO. LCM-1	APPD.	DATE	DWG. NO.	SHEET 1 OF 1
												1024600K1-T			*120248MA	