Features

- · Designed with Zero-Bezel technology
- · Long lasting product cycle
- Multiple mounting options including Rear Mount and VESA mounting
- · Supplied with Projected Capacitive (P-Cap) touch screen

AGDisplays

For over a decade AGDisplays has been a leading provider of high quality LCD enhancement products and services for the industrial markets. We provide a one stop shop with for LCD solutions. Our standard product offerings include a wide range of sizes and combinations. We offer LCD solutions that include NVIS, Coverglass, Touchscreen, High Bright LEDs, Bonding Services, Design Integration, Film Enhancements and more. AGDisplays creates new and enhances existing designs, LCD ruggedization, and simple or complex integration work. Our team's #1 goal is to work hard to become your trusted partner.



SPECIFICATION

Case/frame color	Black/Gray
Display type	Active matrix TFT LCD, LED backlight
Diagonal dimension	19"
Aspect ratio	5:4
Active area dimensions	376.32mm(H) × 301.06mm(V)
Display size (mm) WxHxD	437mm(W) × 362mm(H) × 220mm(D)
Resolution	1280 × 1024 @ 60 Hz
Supported Resolutions	640 x 480, 720 x 400, 832 x 624, 800 x 600, 1024 x 768, 1152 x 864, 1280 x 960, 1280 x 1024
Power	External Adapter: 100-240 VAC, 50-60 Hz Input Voltage Range: +12VDC ±5%
Brightness (std)	250 cd/m2
Response time (std)	5 ms
View angle (from center)	Horizontal (left/right): 160° (80°/80°)
	Vertical (up/down): 160° (80°/80°)
Contrast ratio	1000:1 typ
Input video formats	RGB Analog / DVI Video
Input video signal con- nectors	VGA / DVI-D

Display colors	16.7M
Power consumption (std)	25W
Temperature	Operating: 0°C to 40°C (32°F to 104°F)
	Storage: -20°C to 60°C (-4°F to 140°F)
Humidity	Operating: 20%-80%
	Storage: 10%-90%
MTBF	50,000 hours
Weight (approx)	Monitor: 8.5kg / Shipping 10.5kg
Warranty	1 Year
OSD	Control (back): Menu, Up, Down, Auto, Power
Mounting options	Desktop, VESA Mount 75 mm & 100 mm
Touch Type	P-Cap
Touch Interface	USB
Touch Points	10
Agency approvals	FCC, CE, UL, CCC

