Features

- · Slim profile with unique narrow borders
- · Long lasting product cycle
- Multiple mounting options including Rear Mount and VESA mounting
- · Supplied with Surface Acoustic Wave (SAW) touch screen



For over a decade AGDisplays has been a leading provider of high quality LCD enhancement products and services for the industrial markets. We provide a one stop shop with for LCD solutions. Our standard product offerings include a wide range of sizes and combinations. We offer LCD solutions that include NVIS, Coverglass, Touchscreen, High Bright LEDs, Bonding Services, Design Integration, Film Enhancements and more. AGDisplays creates new and enhances existing designs, LCD ruggedization, and simple or complex integration work. Our team's #1 goal is to work hard to become your trusted partner.





SPECIFICATION

Case/frame color	Black
Display type	Active matrix TFT LCD, LED backlight
Diagonal dimension	10.4"
Aspect ratio	4:3
Active area dimensions	211.2mm(H) × 158.4mm(V)
Display size (mm) WxHxD	254.2mm(W) × 201.2mm(H) × 39.4mm(D)
Resolution	800 × 600 @ 60 Hz
Display colors	16.7M
Power	External Adapter: 100-240 VAC, 50-60 Hz Input Voltage Range: +12VDC ±5%
Brightness (std)	250 cd/m2
Response time (std)	10.4 ms
View angle (from center)	Horizontal (left/right): 170° (85°/85°) Vertical (up/down): 160° (80°/80°)
Contrast ratio	1000:1 typ
Input video formats	RGB Analog
Input video signal con- nectors	VGA

Agency approvals	FCC, CE, CCC
Power consumption (std)	10 W
Temperature	Operating: 0°C to 40°C (32°F to 104°F) Storage: -20°C to 60°C (-4°F to 140°F)
Humidity	Operating: 20%-80% Storage: 10%-90%
MTBF	50,000 hours
Weight (approx)	Monitor 7kg/Shipping 9 kg
Warranty	1 Year
OSD	Control (back): Menu, Up, Down, Auto, Power
Mounting options	100mm or 75mm VESA mounting,open bracket mounting
Touch Technology	SAW
Touch Interface	Dual Serial RS232 / USB

