

Features

- Slim profile with unique narrow borders
- Long lasting product cycle
- Multiple mounting options including Rear Mount and VESA mounting
- Supplied with Surface Acoustic Wave (SAW) touch screen

AGDisplays

For over a decade AGDisplays has been a leading provider of high quality LCD enhancement products and services for the industrial markets. We provide a one stop shop with for LCD solutions. Our standard product offerings include a wide range of sizes and combinations. We offer LCD solutions that include NVIS, Coverglass, Touchscreen, High Bright LEDs, Bonding Services, Design Integration, Film Enhancements and more. AGDisplays creates new and enhances existing designs, LCD ruggedization, and simple or complex integration work. Our team's #1 goal is to work hard to become your trusted partner.



SPECIFICATION

Case/frame color	Black
Display type	Active matrix TFT LCD, LED backlight
Diagonal dimension	15.0"
Aspect ratio	4:3
Active area dimensions	304.128mm(H) x 228.096mm(V)
Display size (mm) WxHxD	344.5mm(W) x 268.5mm(H) x 39mm(D)
Resolution	1024 x 768 @ 60 Hz
Other supported resolutions	640 x 480, 720 x 400, 800 x 600, 832 x 624
Power	External Adapter: 100-240 VAC, 50-60 Hz Input Voltage Range: +12VDC ±5%
Brightness (std)	250 cd/m ²
Response time (std)	10.4 ms
View angle (from center)	Horizontal (left/right): 150° (75°/75°) Vertical (up/down): 130° (70°/60°)
Contrast ratio	500:1
Input video formats	RGB Analog
Input video signal connectors	VGA

Agency approvals	FCC, CE, CCC
Power consumption (std)	2CCFL: 30 W
Temperature	Operating: 0°C to 40°C (32°F to 104°F) Storage: -20°C to 60°C (-4°F to 140°F)
Humidity	Operating: 20%-80% Storage: 10%-90%
MTBF	50,000 hours
Weight (approx)	Monitor 4.6kg/ Shipping 7kg
Warranty	1 Year
OSD	Control (back): Menu, Up, Down, Auto, Power
Mounting options	100mm or 75mm VESA mounting, open bracket mounting
Display colors	16.2M
Touch Type	SAW
Touch Interface	Dual Serial RS232 / USB

Note: Specifications may be subject to change without prior notice. Actual product appearance may differ from photo on datasheet.

