Features

- · Low maintence touchmonitor solution
- · Long lasting product cycle
- Multiple mounting options including Rear Mount and VESA mounting
- · Supplied with Projected Capacitive (P-Cap) touch screen



For over a decade AGDisplays has been a leading provider of high quality LCD enhancement products and services for the industrial markets. We provide a one stop shop with for LCD solutions. Our standard product offerings include a wide range of sizes and combinations. We offer LCD solutions that include NVIS, Coverglass, Touchscreen, High Bright LEDs, Bonding Services, Design Integration, Film Enhancements and more. AGDisplays creates new and enhances existing designs, LCD ruggedization, and simple or complex integration work. Our team's #1 goal is to work hard to become your trusted partner.





SPECIFICATION

Case/frame color	Black/gray
Display type	Active matrix TFT LCD, LED backlight
Diagonal dimension	15.0"
Aspect ratio	4:3
Active area dimensions	304.128mm(H) × 228.096mm(V
Display size (mm) WxHxD	364mm(W) × 288mm(H) × 40.8mm(D)
Resolution	1024 × 768 @ 60 Hz
Other supported resolutions	640 x 480, 800 x 600, 832x 624, 1024 x 768
Power	External Adapter: 100-240 VAC, 50-60 Hz Input Voltage Range: +12VDC ±5%
Brightness (std)	350 cd/m2
Response time (std)	8 ms
View angle (from center)	Horizontal (left/right): 160° (80°/80°) Vertical (up/down): 160° (80°/80°)
Contrast ratio	600:1
Input video formats	RGB Analog/DVI Video
Input video signal con- nectors	VGA/DVI-D

Agency approvals	FCC, CE, CCC
Power consumption (std)	LED: 20 W
Temperature	Operating: 0°C to 40°C (32°F to 104°F) Storage: -20°C to 60°C (-4°F to 140°F)
Humidity	Operating: 20%-80% Storage: 10%-90%
MTBF	50,000 hours
Weight (approx)	Monitor: 8.5kg / Shipping 10.5kg
Warranty	1 Year
OSD	Control (back): Menu, Up, Down, Auto, Power
Display colors	16.7M
Mounting options	75mm VESA mounting, open bracket mounting
Touch Type	P-Cap
Touch Interface	USB

FOUSPLAYS