



220 Huff Ave, Suite 400
Greensburg, PA 15601



PH: (724) 552-4904
F: (724) 552-4905




sales@agdisplays.com
agdisplays.com



Advanced LCD Solutions Specialist

SPECIALTY DISPLAYS



**3D DISPLAYS
TRANSPARENT DISPLAYS
WHITE/BLACKBOARDS
SPECIALTY DIGITAL SIGNAGE**

About Us



For over a decade AGDisplays has been a leading provider of high quality LCD enhancement products and services for the industrial markets. We lead the way in offering an extensive range of custom panel solutions that improve standard display attributes while maximizing performance in any environment. The AGDisplays teams are experts in LCDs, from building simple or complex designs to integration work including ruggedization.

In our 124,000 sq. foot facility, we offer over 800 off the shelf products that include tablets, open and closed frame LCDs and much more. Our knowledge in innovative LCD technology and our high-quality control standards separate us from the rest. At AGDisplays, our teams have a true commitment to becoming your trusted partner.



OUR SERVICES

- Off The Shelf LCD Products
- NVIS Integration and Design
- OCA, Optical & Bonding Services
- Custom LED Integration & Design
- Touch Screen Integration & Design
- Custom Glass Supply Services
- Turnkey & Design Services
- EMI Shielding & Design

- Film Enhancements & Repolarization
- Certificated FAA Part 145 Repair Station
- Component Assembly & Integration
- LCD Controller, Cabling & Design
- Testing/Certification of EOL Panels
- Drop-in Replacement
- Industrial Repair Program
- Zero Dead Pixel Inspection

Industries Served



MILITARY



AVIONICS



HOTEL



MARINE



MARKETING



MEDICAL



RESTAURANT



RETAIL



TRANSPORTATION



Applications



3D PHOTOGRAPHY
3D VIDEO
ADVERTISING
CAD/CAM APPLICATIONS
DESIGN AND ENGINEERING
DIGITAL SIGNAGE
MARKET RESEARCH STUDIES
PRODUCT INTRODUCTION
SIMULATION APPLICATIONS
SPECIAL EVENTS

NOTE: specifications subject to change without notice.

3D Holographic Fan Display



AG3DH-V9

Size	42 cm	Viewing Angle	150°
Resolution	400x224	Display Diameter	420 mm
3D Effect Format	MP4/GIF	Content	JPG, MP4, AVI, RMVB, GIF (directly read video or picture file)
Hologram Video	Normal video with black background	Hologram	Support multiple video
Content Update	SD card (USB, Wifi optional)	Frame Material	ABS+PC+Aluminum
Installation	Wall mounted	Application	Indoor Advertising
Weight	1.5 KG	Accessory	Power supply cable, user manual, remote control, 12V mobile power supply
Interface	VGA/HDMI/USB	Interface	HDMI/USB/SD
Touchscreen	Infrared touch screen (touch foil, capacitive)	Touchscreen	Infrared touch screen (touch foil, capacitive)
Touch Dots	1/2/4/6 dots (optional)	Touch Dots	2 dots
Power	140W	Power	120W

NOTE: specifications subject to change without notice.

3D Holographic Displays




AC3DH-V1

Sizes Available	19" 22" 27" 32" 42" 46" 47" 50" 55" 58" 65" 70" 84"
Unit Size	430x383.5x285 mm
Brightness	1000 nits
Contrast Ratio	700:1
Resolution	1280x1024
Consumption	≤40W
Power	DC12V/3A
Ratio	4:3



AC3DH-V2

Sizes Available	22" 32" 42" 55"
Unit Size	430x383.5x285 mm
Brightness	1000 nits
Contrast Ratio	700:1
Resolution	1280x1024
Consumption	≤40W
Power	DC12V/3A
Ratio	4:3



AC3DH-V3

Sizes Available	19" 22" 27" 32" 42" 46" 47" 50" 55" 58" 65" 70" 84"
Unit Size	430x383.5x285 mm
Brightness	1000 nits
Contrast Ratio	700:1
Resolution	1280x1024
Consumption	≤40W
Power	DC12V/3A
Ratio	4:3



AC3DH-V4

Sizes Available	19" 22" 27" 32" 42" 46" 47" 50" 55" 58" 65" 70" 84"
Unit Size	430x383.5x285 mm
Brightness	1000 nits
Contrast Ratio	700:1
Resolution	1280x1024
Consumption	≤40W
Power	DC12V/3A
Ratio	4:3

NOTE: specifications subject to change without notice.

3D Holographic Displays



AC3DH-V5

Sizes Available	19" 22" 27" 32" 42" 46" 47" 50" 55" 58" 65" 70" 84"
Unit Size	430x383.5x285 mm
Brightness	1000 nits
Contrast Ratio	700:1
Resolution	1280x1024
Consumption	≤40W
Power	DC12V/3A
Ratio	4:3




AC3DH-V6

Sizes Available	19" 22" 27" 32" 42" 46" 47" 50" 55" 58" 65" 70" 84"
Unit Size	430x383.5x285 mm
Brightness	1000 nits
Contrast Ratio	700:1
Resolution	1280x1024
Consumption	≤40W
Power	DC12V/3A
Ratio	4:3



AC3DH-V7

Sizes Available	19" 22" 27" 32" 42" 46" 47" 50" 55" 58" 65" 70" 84"
Unit Size	430x383.5x285 mm
Brightness	1000 nits
Contrast Ratio	700:1
Resolution	1280x1024
Consumption	≤40W
Power	DC12V/3A
Ratio	4:3




AC3DH-V8

Sizes Available	19" 22" 27" 32" 42" 46" 47" 50" 55" 58" 65" 70" 84"
Unit Size	430x383.5x285 mm
Brightness	1000 nits
Contrast Ratio	700:1
Resolution	1280x1024
Consumption	≤40W
Power	DC12V/3A
Ratio	4:3

NOTE: specifications subject to change without notice.

Glasses Free 3D Displays



AG550KM-3D04N-NUU-V1

Sizes Available	40" 42" 46" 47" 55"
Unit Size	55"
Brightness	400 nits
Contrast Ratio	4000:01
Resolution	3840x2160
Working Temperature	0°C~50°C
Interface	--
Ratio	16:09

AG550KM-3D04N-NUU-W1

Sizes Available	32" 55" 65"
Unit Size	55"
Brightness	450 nits
Contrast Ratio	5000:1
Resolution	3840x2160
Working Temperature	-5°C-45°C
Interface	VGA/HDMI/USB
Ratio	16:9



AG550KM-3D04N-NUU-A1

Sizes Available	32" 55" 65"
Unit Size	55"
Brightness	450 nits
Contrast Ratio	5000:1
Resolution	3840x2160
Working Temperature	-5°C-45°C
Interface	HDMI/USB/SD
Ratio	16:9

NOTE: specifications subject to change without notice.

Transparent LCD Displays



AG460HM-T04N-ITG-W1

Sizes Available	42" 46" 55" 65" 70"
Unit Size	46"
Brightness	450-750 nits
Contrast Ratio	5000:1
Resolution	1080x1920
Interface	VGA/HDMI/USB
Power	140W
Ratio	16:9



AG460HM-T04N-ITG-A1

Sizes Available	42" 46" 55" 65" 70"
Unit Size	46"
Brightness	450-750 nits
Contrast Ratio	5000:1
Resolution	1080x1920
Interface	HDMI/USB/SD
Power	120W
Ratio	16:9



AG420HM-TOUN-NUU-V1

Sizes Available	22" 32" 42" 46" 55"
Unit Size	42"
Response Time	8 ms
Input Voltage	AC100~240V 50/60 HZ
Resolution	1920x1080
Video Format	AVI/MPEG1/MPEG2/MPEG4
Viewing Angle	178°/178°
Ratio	16:9



AG420HM-TOUN-NUU-V2

Sizes Available	22" 32" 42" 46" 55"
Unit Size	42"
Response Time	8 ms
Input Voltage	AC100~240V 50/60 HZ
Resolution	1920x1080
Video Format	AVI/MPEG1/MPEG2/MPEG4
Viewing Angle	178°/178°
Ratio	16:9

NOTE: specifications subject to change without notice.

Featured Bus Signage



AG150TM-DS03N-NUU-V1

Size	15"
Max Resolution	1280 x 1024
Colors	16.7M
Brightness	350
Response Time	8s
Contrast Ratio	450:1
Viewing Angle	178°
Using Life	60,000 hrs
Display Area (HxV)	298.7x165.94 mm
Dot Pitch (HxW)	0.264x0.264 mm

Power Supply	AC 110V - 240V, 50/60HZ
Speaker	10Wx2
Ratio	4:3
Audio Formats	MP3
Photo Formats	JPG,bmp
Audio Output	Stereo L/R, 5Wx2, 8Ω
Storage Temp	-7°-65°C
Working Temp	-5°-65°C
Interface	USB, HDMI, VGA
Certifications	FCC, RoHS, CE

NOTE: specifications subject to change without notice.

Bus Digital Signage



AG150TM-DS03N-NUU-V2

Size	15"
Max Resolution	1280x1024
Colors	16.7M
Brightness	350 nits
Response Time	8s
Contrast	450:1
Viewing Angle	178°/178°
Using Life	60,000h



AG190PM-DS04N-NUU-V1

Size	19"
Sizes Available	15" 17" 19" 22"
Max Resolution	1600x900
Colors	16.7M
Brightness	450 nits
Response Time	8s
Contrast	800:1
Viewing Angle	178°/178°



AG220TM-DS03N-NUU-V1

Size	22"
Sizes Available	15" 17" 19" 22"
Max Resolution	1280x1024
Colors	16.7M
Brightness	350 nits
Response Time	8s
Contrast	450:1
Viewing Angle	178°/178°




AG170TM-DS03N-NUU-V1

Size	17"
Max Resolution	1280x1024
Colors	16.7M
Brightness	350 nits
Response Time	8s
Contrast	450:1
Viewing Angle	178°/178°
Using Life	60,000h

NOTE: specifications subject to change without notice.

LCD Blackboard



AG060HM-BB04N-PTG-W1

Screen Sizes Available	65", 70", 75", 84"	Power Consumption	≤260W
LCD Resolution	1920x1080	Lifetime	50,000 hours
Size	4500 (W) x 1400 (H) x 70 (D) mm	Power	100-240V, 50/60Hz
Brightness	450 nits	Wall Mounts	Equipped
Display Scale	16:09	Touch Technology	Capacitive Touch
Viewing Angle	178°/178°	Touch Type	10 points
Contrast	4000:1	Surface Material	5mm physical tempered glass (7 anti-glare optional)
Backlight Type	LED	Communication Port	USB 2.0
Video Format	PAL/SECAM	Operating System	Windows, Linux, Android
Sound Output Power	2x30W	Power Supply	USB 5.0V powered directly

NOTE: specifications subject to change without notice.

Interactive Whiteboards



AG650HV-CF03N-ITC-V1

Size	65" LED backlit
Resolution	1920x1080
Active Area	1428.48 (H) x 803.52 (V) mm
Brightness	350 nits
Contrast Ratio	5000:1
Viewing Angle	178°/178°
Product Size	1516.50 (H) x 930.46 (V) x 110.8 (D) mm
Power	192 W



AG700HV-CF03N-ITC-V1

Size	70" LED backlit
Resolution	1920x1080
Active Area	1538.88 (H) x 865.62 (V) mm
Brightness	350 nits
Contrast Ratio	5000:1
Viewing Angle	178°/178°
Product Size	1633.1 (H) x 997.7 (V) x 112.8 (D) mm
Power	196 W



AG840KV-CF03N-ITC-V1

Size	84.04" LED backlight
Resolution	3840x2160
Active Area	1860.48 (H) x 1046.52 (V) mm
Brightness	350 nits
Contrast Ratio	1400:1
Viewing Angle	178°/178°
Product Size	1950 (H) x 1150 (V) x 89.5 (D) mm
Power	450 W



AG980KV-CF04N-ITC-V1

Size	98" LED backlit
Resolution	3840x2120
Active Area	1555 (H) x 875 (V) mm
Brightness	450 nits
Contrast Ratio	1300:1
Viewing Angle	178°/178°
Product Size	--
Power	530 W

NOTE: specifications subject to change without notice.

